

SPIDER-U Series

Spider like multiple socket for home and office application.

- Line Interactive UPS Design
- Energy Saving Green Topology
- Tri-direction Hanger Flexibility
- Cold Start Function
- Overload, Surge, Short Circuit Protection



SPD-650-1000U

Specifications

Model	SPD-650U	SPD-850U	SPD-1000U
Configuration			
Capacity (VA)	650 VA	850 VA	1000 VA
Capacity (Watts)	390 W	510 W	550 W
Form	Office Type		
Input			
Voltage	220 / 230 / 240 VAC		
Input Voltage Range	140 - 300 VAC		
Input Frequency Range	50 Hz / 60 Hz (Auto Sensing)		
Output			
Waveform	Simulated Sine Wave		
Voltage	220 / 230 / 240 VAC		
Frequency	50 Hz / 60 Hz ± 0.5 Hz		
Transfer Time	2 - 4 ms (Typical)		
Protection			
Full Protection	Overload, Surge, Short Circuit		
Tel Communication	RJ11 / RJ45 : U model		
Battery			
Type	12V 7.2Ah	12V 9Ah	
Quantity	1	1	
Sealed, Maintenance Free	Yes		
Typical Recharge Time	8 hr to 90%		
Management & Communication			
Indicator	LED Panel, LCD Panel (Option)		
Communication Port	USB B type : U model		
Physical			
Dimensions (WxDxH) (mm)	232 x 285 x 103		
Weight (kgs)	7	7.7	7.7
Shipping Dimensions (mm)	302 x 354 x 176		
Shipping Weight (kgs)	7.5	8.2	8.2
Alarm			
Overload / Fault	Continuous Beeping		
Battery Mode	Beep every 4 seconds		
Low Battery	Beep every 0.5 second		
Environment			
Operating Humidity	0-90 % RH at 0-40°C (Non-condensing)		
Audible Noise	Less than 40 dB		

* N series without tel communication, USB

* Specifications are subject to change without further notice.

* Specifications are for reference, actual information should be based on real product.

OUTPUT RECEPTACLE OPTION



TYPE B TYPE E TYPE F TYPE G TYPE I TYPE IEC