

KING RM Series

Complete protection for internet computers and advanced servers.

- Line-Interactive UPS with Rack Mounting Design
- Simulated Sinewave Output
- Colorful diagram LCD for better UPS status indication
- Build-in AVR aimed for Fluctuating Voltage Problem
- EMI / RFI Noise Filter Applied
- Surge, Short Circuit, Overload Protections



KIN-600-1000AP RM



KIN-1200-1500AP RM



KIN-2200-3000AP RM

Specifications

Model	KIN-600AP RM	KIN-1000AP RM	KIN-1200AP RM	KIN-1500AP RM	KIN-2200AP RM	KIN-3000AP RM
Configuration						
Capacity (VA)	600 VA	1000 VA	1200 VA	1500 VA	2200 VA	3000 VA
Capacity (Watts)	480 W	800 W	960 W	1200 W	1760 W	2400 W
Form	Rack Type					
Input						
Voltage	100 / 110 / 115 / 120 VAC or 220 / 230 / 240 VAC					
Input Voltage Range	75 - 150 or 165 - 300 VAC					
Input Frequency Range	50 Hz / 60 Hz (Auto Sensing)					
Output						
Waveform	Simulated Sine Wave					
Voltage	100 / 110 / 115 / 120 VAC or 220 / 230 / 240 VAC					
Frequency	50 Hz / 60 Hz ± 0.5 Hz					
Transfer Time	2 - 4 ms (Typical)					
Protection						
Full Protection	Overload, Surge, Short Circuit					
Tel Communication	RJ11 / RJ45					
Battery						
Type	6V 7Ah	6V 8Ah	12V 7Ah	12V 9Ah	12V 7Ah	12V 9Ah
Quantity	2	3	2	2	4	4
Sealed, Maintenance Free	Yes					
Typical Recharge Time	8 hr to 90%					
Management & Communication						
Indicator	LED Panel		LCD Panel			
Communication Port	RS232 or USB B type		RS232, USB B type			
SNMP Solt	NA		Option			
Physical						
Dimensions (WxDxH)(mm)	380 x 365 x 42		428 x 357 x 84		428 x 353 x 130	428 x 486 x 130
Weight (kgs)	9.4	11.5	16.3	16.3	28.4	32.7
Shipping Dimensions (mm)	478 x 438 x 161		574 x 522 x 202		574 x 522 x 248	663 x 583 x 285
Shipping Weight (kgs)	11	13	19.3	19.3	31.1	36
Alarm						
Overload / Fault	Continuous Beeping					
Battery Mode	Beep every 2 seconds					
Low Battery	Beep every 0.5 second					
Environment						
Operating Humidity	0-90 % RH at 0-40°C (Non-condensing)					
Audible Noise	Less than 40 dB					

* Specifications are subject to change without further notice.

* Specifications are for reference, please refer to information based on real product.

OUTPUT RECEPTACLE OPTION



TYPE B



TYPE E



TYPE F



TYPE G



TYPE I



TYPE IEC