

DC UPS

Extraordinary DC UPS provide DC output for electronic application.



DC - 12V-48V

Feature

- DC Output UPS Design
- Wide Input Voltage Range
- Cold Start Function
- Energy Saving Green Topology
- Overload, Surge, Short Circuit Protection

Specification

Model	DC 12V	DC 18V	DC 24V	DC 48V
Configuration				
Capacity (Watts)	30 W	30 W	30 W	30 W
Input				
Voltage Range	86 - 276 VAC			
Frequency Range	50 Hz / 60 Hz			
Output (On Battery)				
Voltage Regulation	± 15 %	± 10 %	± 10 %	± 10 %
Transfer Time (ms)	5			
Battery				
Type	12V 5Ah	12V 5Ah	12V 5Ah	12V 5Ah
Number	1	1	1	1
Typical Recharge Time	8 hrs to 90 % Capacity			
Protection				
Full Protection	Overload, Short Circuit, Surge			
Physical				
Dimension (WxDxH) (mm)	267 x 155 x 64			
Weight (kgs)	2.4			
Shipping Dimension (mm)	359 x 198 x 79			
Shipping Weight (kgs)	2.6			
Management & Communication				
Indicator	LED Indicator			
Alarm				
Overload	Continuous Beeping			
Battery Mode	Beep every 4 seconds			
Low Battery	Beep every 0.5 seconds			
Environment				
Operating Humidity	0-95 % RH at 0-40°C (Non-condensing)			
Audible Noise	Less than 40 dB			

* Specifications are subject to change without further notice.

* Specifications are for reference, actual information should be based on real product.