

IMPERIAL Series

High quality output plus elegant design protect PC and workstation.

- Line Interactive UPS Design
- Energy Saving Green Topology
- Automatic Voltage Regulator (AVR)
- Advance Digital Microprocessor Control
- Simple and Clear Digital Indicator (IMD model)
- Overload, Surge, Short Circuit Protection



IMD-1025-3000AP

IMP-1025-3000AP

Specifications

Model	IMP-1025AP	IMP-1200AP	IMP-1500AP	IMP-2000AP	IMP-3000AP
Configuration					
Capacity (VA)	1025 VA	1200 VA	1500 VA	2000 VA	3000 VA
Capacity (Watts)	615 W	720 W	900 W	1200 W	1800 W
Form	Tower Type				
Input					
Voltage	100 / 110 / 120 VAC or 220 / 230 / 240 VAC				
Input Voltage Range	75 - 150 or 165 - 300 VAC				
Input Frequency Range	50 Hz / 60 Hz (Auto Sensing)				
Output					
Waveform	Simulated Sine Wave				
Voltage	100 / 110 / 120 VAC or 220 / 230 / 240 VAC				
Frequency	50 Hz / 60 Hz ± 0.5 Hz				
Transfer Time	2 - 4 ms (Typical)				
Protection					
Full Protection	Overload, Surge, Short Circuit				
Tel Communication	RJ11 / RJ45 : AP model				
Battery					
Type	12V 7.2Ah		12V 9Ah		12V 9Ah
Quantity	2		2		3
Typical Recharge Time	6-8 hr to 90%				
Management & Communication					
Indicator	LED Control Panel : IMP model Digital Control Panel : IMD model				
Communication Port	USB B type : AP model				
Physical					
Dimensions (WxDxH) (mm)	130 x 382 x 200				130 x 440 x 200
Weight (kgs)	13.5	13.5	16	16.6	22
Shipping Dimensions (mm)	253 x 488 x 321				253 x 556 x 321
Shipping Weight (kgs)	15.5	15.5	18	18.6	24
Alarm					
Overload / Fault	Continuous Beeping				
Battery Mode	Beep every 2 seconds				
Low Battery	Beep every 0.5 second				
Environment					
Operating Humidity	0-90 % RH at 0-40°C (Non-condensing)				
Audible Noise	Less than 40 dB				

* IMD Series are same specification with IMP Series, but in Digital Indicator.

* Specifications are subject to change without further notice.

* Specifications are for reference, actual information should be based on real product.

OUTPUT RECEPTACLE OPTION

