

SMART RT Series

Upgraded SRT pure sinewave are the best series for home and small server.

- Line Interactive UPS Design
- Pure Sinewave Output
- Automatic Voltage Regulator (AVR)
- Hot Swappable Power Battery Design
- Advance Battery Management (ABM)
- Overload, Surge, Short Circuit Protection



SRT-1000-3000A

Specifications

Model	SRT-1000A	SRT-1500A	SRT-2000A	SRT-3000A
Configuration				
Capacity (VA)	1000 VA	1500 VA	2000 VA	3000 VA
Capacity (Watts)	900 W	1350 W	1800 W	2700 W
Form	Rack and Tower Type			
Input				
Voltage	220 / 230 / 240 VAC			
Input Voltage Range	150 - 310 VAC			
Input Frequency Range	50 Hz / 60 Hz (Auto Sensing)			
Output				
Waveform	Pure Sine Wave			
Voltage	220 / 230 / 240 VAC			
Transfer Time	2-4 ms (Typical)			
Protection				
Full Protection	Overload, Surge, Short Circuit, EMI / RFI Filter			
Tel Communication	RJ11 / RJ45			
Battery				
Type	12V 9Ah	12V 7Ah	12V 9Ah	12V 9Ah
Quantity	2	4	4	6
Sealed, Maintenance Free	Yes			
Typical Recharge Time	3 hr to 90%			
Management & Communication				
Indicator	LED Panel			
Communication Port	RS232 , USB B type, SNMP (Option)			
Physical				
Dimensions (WxDxH) (mm)	428 x 431 x 84	428 x 562 x 84		428 x 668 x 84
Weight (kgs)	16.7	24	27.5	36.8
Shipping Dimensions (mm)	577 x 590 x 211	720 x 577 x 211		826 x 577 x 211
Shipping Weight (kgs)	20.5	27.9	31.5	41.6
Alarm				
Overload / Fault	Continuous Beeping			
Battery Mode	Beep every 4 seconds			
Low Battery	Beep every 1 second			
Environment				
Operating Humidity	0-90 % RH at 0-40°C (Non-condensing)			
Audible Noise	Less than 50 dB			

* Specifications are subject to change without further notice.

* Specifications are for reference, actual information should be based on real product.

OUTPUT RECEPTACLE OPTION



TYPE B



TYPE E



TYPE F



TYPE G



TYPE I



TYPE IEC