

TAP-CHANGE AVR



TCA-600-3000

Main Feature

Build-in Automatic Voltage Regulator(AVR)

Attached with AVR stabilize fluctuate voltage problem

Power protection on critical device

Surge, short circuit and overload protection assurance power safety

Clear UPS status display

Attached LED shows up UPS status

Auto Self-diagnose and alarm warning

Self-test diagnose and emergency alarm warning

Support telecom equipment

Connectable through RJ45, RJ11 port (Option)

Specification

Model	TCA-600	TCA-1200	TCA-2000	TCA-3000
Power Rating	300 W	600 W	1000 W	1500 W
Phase	Single Phase			
AC Input				
Frequency	50Hz or 60Hz			
Voltage	1φ 2W			
Range	110 / 120 Vac ± 15% 220 / 230 / 240 Vac ± 15%			
AC Output				
Voltage	1φ 2W			
Voltage Regulation	110 / 120 Vac ± 5% (Typical) 220 / 230 / 240 Vac ± 5% (Typical)			
Frequency	50 Hz / 60 Hz Following Input			
Efficiency	> 95 %			
Protection				
Full Protection	Overload, Short Circuit, Surge			
Tel Communication	RJ11 / RJ45			
Management & Communication				
Indicator	LED Panel			
Physical				
Dimension (WxDxH) (mm)	123 x 136 x 102			
Weight (kgs)	1.45	1.6	1.8	2.1
Shipping Dimension (WxDxH)(mm)	145 x 195 x 120			
Shipping Weight (kgs)	1.65	1.8	2	2.3
Environment				
Operating Humidity	0-95 % RH at 0-40°C (Non-condensing)			
Audible Noise	Less than 40 dB			

* Specifications are subject to change without further notice.

* Specifications are for reference, please refer to information based on real product.

20240420