

PM-12-17 (12V 17Ah)

- Flexible Installation and Maintenance-Free Lead-Acid Battery
- Under 25°C, the Designed Floating life is up to 3~5 years
- Under Normal Circumstances, the Battery Will Remain Sealed;
When the Internal Pressure Is High, It Will Reduce the Pressure
- International Standard Classification IEC 61056 and GB/T 19639
- Applied to Electronic Equipment such as Telecommunication,
Medical Treatment, Lighting, etc.



Specification

PM-12-17 (12V 17Ah)			
Capacity			
Nominal Capacity	17Ah		
Voltage & Current			
Rated Voltage	12V		
Max. Discharge Current	270A(5s)		
Charge Voltage(25°C)	Float	Charge voltage	Temp. Coefficient
	Equalization	2.25~2.30V/cell	-3mV/ single cell /°C
	Cycle	2.35~2.40V/cell	-4mV/ single cell /°C
		2.40~2.50V/cell	-5mV/ single cell /°C
Max.Charging Current(25°C)	5.1A		
Internal Resistance(25°C)	Approx 16mΩ		
Temperature			
Operating Temp. Range	Discharge : -20~55°C(-4 ~ 131°F)		
	Charge : 0~40°C(32 ~ 104°F)		
	Storage : -15~50°C(5 ~ 122°F)		
Nominal Operating Temp. Range	25±3°C (77±5°F)		
Effect of temp. to Capacity	40°C (104°F) 103%		
	25°C (77°F) 100%		
	0°C (32°F) 86%		
Self Discharge	≤ 3%/month @ 25°C		
Physical			
Dimension	Length : 181.5±2mm (7.15 inches)		
	Width : 76.5±1mm (3.01 inches)		
	Container Height : 167.5±2mm (6.59 inches)		
	Total Height : 167.5±2mm (6.59 inches)		
Approx Weight	5.35kg (11.79 lbs)		
Container Material	ABS		
Terminal	T3		